





















Wilbert TowerCranes GmbH

Crane type: WT 650 *e.tronic*

Description: Packing list

Pos.	Qty.	Description	Package (not to scale)	Length [m]	Width [m]	Height [m]	Weight [kg]	Volume [m ³]
1	1	Tower head section compl. with various stay rods		13.38	2.44	2.49	20,880	81.36
	Pos. 1 fragmented	Lower part of the tower head section with slewing frame		4.73	2.44	2.49	13,200	28.73
		Upper part of the tower head section compl.		10.12	2.03	2.13	7,400	43.76
		Upper part of the tower head section, part 1		6.00	2.03	2.13	3,600	25.93
		Upper part of the tower head section, part 2		4.43	2.06	1.38	2,650	12.61
		Platform tower head section		2.10	1.60	0.42	160	1.41
		Ladder upper part of the tower head section, part 2		2.21	0.77	0.74	110	1.27
2	1	Cab with cab platform		3.28	1.90	2.45	1,360	15.27
3	1	Counter jib 1		6.91	2.44	0.72	3,250	12.12
4	1	Counter jib 2		6.90	2.44	0.72	3,350	12.10
5	1	Counter jib 3		13.72	2.44	1.12	7,500	37.24
6	1	Machine platform HFU 110-80 with hoist rope		2.30	5.40	1.99	7,500	24.67
7	1	Jib section 1 with trolley gear		12.77	2.02	2.64	4,900	67.94
8	0-1 *	Jib section 2		12.80	1.96	2.45	4,100	61.47
9	0-1 *	Jib section 3		12.80	1.96	2.44	3,200	61.21
10	1	Jib section 4		12.80	1.96	3.09	3,240	77.47
11	1	Jib section 5		5.36	1.48	1.89	1,600	15.00
12	0-1 *	Jib section 6		5.39	1.48	1.89	1,400	15.08
13	0-1 *	Jib section 7		7.83	1.48	1.89	1,700	21.91
14	0-3 *	Jib section 8		5.31	1.48	1.89	1,000	14.84
15	0-1 *	Jib section 9		7.73	1.48	1.89	1,050	21.61
16	1	Rope swivel crossbeam		0.79	1.55	0.42	290	0.51
17	1	Trolley		2.16	2.22	1.79	1,300	8.55
18	1	Load hook		1.26	0.27	2.19	1,000	0.73

Pos.	Stück	Description	Package (not to scale)	Length [m]	Width [m]	Height [m]	Weight [kg]	Volume [m³]
19	0-1 *	Stay rack		8.01	1.92	1.11	705	17.09
20	1	Stay lug Jib "28"		0.74	0.06	0.26	78	0.01
21	0-1 *	Stay lug Jib 2 "9"		2.42	0.29	0.32	198	0.22
22	1	Stay lug Jib 5 "6"		2.42	0.24	0.32	192	0.19
23	1-2 *	Jib Stay 2010 mm "1"		2.35	0.13	0.32	194	0.10
24	0-1 *	Jib Stay 2300 mm "8"		2.64	0,13	0.28	223	0.10
25	0-1 *	Jib Stay 3281 mm "5"		3.62	0.13	0.26	271	0.12
26	0-1 *	Jib Stay 4450 mm "7"		4.79	0.13	0.28	333	0.17
27	0-1 *	Jib Stay 5392 mm "4"		5.73	0.13	0.28	381	0.21
28	0-1 *	Jib Stay 5598 mm "3"		5.94	0.13	0.28	391	0.22
29	4-7 *	Jib Stay 6540 mm "2"		6.88	0.13	0.26	437	0.23
30	2	Stay rod (counterjib) 3280 mm "4"		3.60	0.09	0.24	149	0.08
31	0-2 *	Stay rod (counterjib) 6130 mm "3"		6.45	0.09	0.24	230	0.14
32	2	Stay rod (counterjib) 6470 mm "2"		6.79	0.09	0.26	242	0.16
33	2	Stay rod (counterjib) 9150 mm "1"		9.47	0.07	0.26	318	0.17
34	1	Railings (loose parts) two-part counterjib		2.65	1.10	1.76	477	5.13
35	1	Railings (loose parts) three-part counterjib		2.60	1.10	2.17	560	6.21
36	1	Concrete counterweight (under machine platform)		1.20	2.00	0.37	2,000	0.89
37	4-13 *	Concrete counterweight		2.26	1.41	0.36	2,700	1.15